



# Javelin Zero

50W - 400W Spec Sheet

## Overview

Designed specifically for temperature controlled environments, Carbon8Lighting's award winning Javelin Zero LED Linear fitting offers all of the benefits of the standard Javelin2 LED Linear plus some simple innovation that makes it the ideal choice in freezers and cold stores.

By detaching the drive gear and placing it outside the freezer the Javelin Zero gives off less heat inside the temperature controlled environment than any other fitting available. Additionally, in the unlikely event of a driver failure, this can be dealt with very simply, outside the temperature controlled environment. The ultra-efficient Javelin and Javelin Zero Gen2 LED Linear range offers phenomenal value for money, market leading performance and unparalleled reliability.

The Javelin Zero range combines high quality materials, leading edge technology and intelligent design to produce a robust and reliable light fitting that is IP65 rated and can operate in the harshest environments.

## Features & Benefits

- Die-cast Aluminium Housing with UV stabilized powder coating.
- Precision accurate polycarbonate lenses put light where it's wanted.
- IP65 Rated.
- Dali Dimming Control.
- Ultra-efficient performance up to 140lm/W.
- Carbon8's Unique 7 Year Premier Care Warranty Program.
- Suitable for food production areas.

## **Application**





Description: MHB Linear IP65 Recommended Product Location: Industrial and fridge/freezer applications


PRODUCT DETAILS			
Case Material	DIE CAST ALUMINIUM		
Voltage	100-305AC		
IP Rating	IP65		
Typical Lumens per watt	130 lm/w		
Colour Rendering	>70 (>80 available )		
LED Module	Lumileds		
Cable	Artic Cable		
Operating Temperature	-40° to +40°		
Beam angle	30x30°, 60x60° 90x90° 30x100° 140x140°		
Warranty	7 year Premier Care		
Colour Temperature	5000k (4000k & 6500k available special order)		
Power Factor	0.9		
Lens Material	Polycarbonate		
Driver	Meanwell		
OPTIONS			
Occupancy Sensor	<b>√</b>		
Light level sensor	·		
Remote Programmable Sensor	·		
Polycarbonate front	Fitted as standard		
RGB	<b>√</b>		
12-24v	✓		
Emergency	✓		
Fixed Bracket Mounting	✓		

## **Performance Chart**


LED POWER	CIRCUIT WATTS	TYPICAL LUMENS	WEIGHT	DIMENSIONS
60W	55W	7100	4.0 KG'S	107x400x67mm
75W	76W	9600	4.0 KG'S	107x400x67mm
.00W	103W	14300	6.5 KG'S	107x400x67mm
.50W	150W	21400	8.0 KG'S	107x400x67mm
200W	220W	26800	9.0 KG'S	107x400x67mm
800W	300W	39600	11.0 KG'S	218x734x67mm
W00W	440W	57000	16.0 KG'S	218x1034x67mm




## Diagram of Javelin Zero (50W, 75W)








#### Diagram of Javelin Zero (200W)



#### Diagram of Javelin Zero (300W)



## Diagram of Javelin Zero (400W)



The Javelin Zero is covered by Carbon8Lighting's unique 7 Year Premier Care Warranty. Very rarely, even a Carbon8 fitting can become faulty. Should this happen at any point during the 7 year warranty, Carbon8 will send an advance replacement fitting to site, pay up to £500+VAT towards the exchange and collect the swapped fitting from site. As well as minimising down time, this unique warranty reassures customers investing in a Carbon8 product, there will be no hidden cost of ownership.









